

BV 2310

Face Recognition, Fingerprint & Rfid Card Reader For Attendance **And Access Control**














Dual Camera



Wide Camera





Dual Core



Product Name screen Keypad

Operation system

CPU,NPU **RAM ROM**

Binocular camera **Face Capacity** Fingerprint capacity **RFID Card capacity**

Logs

Recognition speed **Recognition Distance**

WDR USB

Powersupply communication Multi Language **OR Code** Dimension

Installation **Working Temperature**

Working Humidity

WDR Ai Dynamic Face recognition Attendance & Access Control terminal

4.3" Touch Screen, HD 1280*720 Touch Key

LINUX 3.10

1.2G Dual core ARM CortexA7, 600G(0.6T)

256MB DDR3

4G EMMC

Real sensor 1/2.9 inch 2MP WDR camera, Sensor 1/5 inch 2mp Live Camera

5,000 faces (20,000 optional)

10,000 fingerprints (50,000 optional)

15,000 cards (50,000 optional)

500,000

<0.5 sec, support single & multi users at same time (upto 5users)

0.5-2.5 meters (0.5 - 1 meters with live face recognition on) Support face recognition under strong/dark light and backlight

USB 2.0, supports imort and export of data

TCP/IP, WiFi, Weigand 26/34 output, Input

English, Spanish, French, Italian, Japanese, Korean

Will Support

155 x 25 x 155mm

Wall Mount

-15 to +45 degree Celsius

20% to 90%

Connect with us:

sales@huaiaccess.com support@huaiaccess.com

www.huaiaccess.com