

BV 2410

Face Recognition, Fingerprint & Rfid Card Reader



5000



15,000



5 Users



Dual Camera



Wide Camera



Dual Core



Wifi/TCP IP





4.3" Display



Model CPU NPU

RAM

ROM Camera

Fill Light

Display

Communication port

Product Size

Power

Working Temperature Working Environment

Verify Method **QR Code Scanner** Face/Card/Password **Fingerprint Capacity**

Logs Capacity Face Recognition Speed

Face Recognition Distance Live Face Detection Relay output Wiegand

Exit button Door Bell

BV-2410

1.2G Dual-Core ARM Cortex-A7 600G (0.6T)

256M DDR3L 4G EMMC

2MP HD Color Camera, 2MP HD Infrared Camera, LED Fill Light and Dual Infrared Fill Light

5 inch HD IPS Touch Screen, Resolution 1280*720 TCP/IP, USB-Type A(Support U disk), Wifi

155mm 133mm 25.5mm

DC 12V, 1A 0-45 C

Under normal light, strong light, **LINUX 3.10**

Face Recognition, ID Card (IC optional),

Support 5000(50000 optional)

10000(100000 Optional)

500,000 < 0.25

0.5-2.5 meters (adjustable) Reject Photo and Video

One set

One set WG 26/34 Output

Support Support

Connect with us:

sales@huaiaccess.com support@huaiaccess.com

www.huaiaccess.com