

## **BV 3610**

## Face Recognition With Human Body Temperature



20,000



20,000



Temperature



5 Users



Wide Camera



8' Display



oo Dual Camera



Dual Core



Wifi/TCP IP



**BIO ASSAY** 



Product Name Screen

Keypad

**Operation System** 

CPU,NPU

**RAM** 

ROM

Binocular Camera

Reader Case Material

**Face Capacity** 

**Record Capacity** 

**Temperature Detection** 

**Recognition Speed** 

**Recognition Distance** 

**WDR** 

USB

Powersupply

Communication

Multi Language

QR Code

Dimension

Installation

Working Temperature

Working Humidity

Face recognition reader with human body temperature detection terminal 8" IPC Touch Screen, HD 800\*1280

Touch Kev

**LINUX 3.10** 

1.2G Dual core ARM CortexA7, 1200 G (1.2T)

512MB DDR3L

**BG EMMC** 

Real sensor 1/2.9 inch 2MP WDR camera, Sensor 1/5 inch 2mp Live Camera

**Aluminium Alloy** 

20,000 faces

5,000,000 logs

Around 0.5 mtr

<0.2 sec, support single & multi users at same time (upto 5 users)

0.5-2.5 meters (0.5-1 meters with live face recognition on)

Support face recognition under strong/dark light and backlight

USB 2.0, supports import and export of data

DC12V,2A

TCP/IP, WiFi, Weigand 26/34 output, Input, 4G (optional), GPS (optional)

English, Spanish, French, Italian, Japanese, Korean

Will Support

155 x 25 x 155mm

Wall Mount, Desktop stand, Medium stand 60cm, High stand 110cm

-15 to +45 degree Celsius

20% to 90%

## Connect with us:

sales@huaiaccess.com support@huaiaccess.com

www.huaiaccess.com